

## Application of your decals / stickers

Your decals / stickers are made up of 3 layers of material as below:



The following is a quick guide on how to apply your decals/stickers, to ensure that they look great and stay secure where you want them.

Before you start we recommend that you have to hand:

- Masking tape
  - Tape measure or rule
  - Rubbing alcohol / isopropyl alcohol (supplied)
  - Plastic squeegee (an old credit card will do)
  - Scissors or craft knife
- ~ If possible wash your car prior to application.
- ~ Ensure that you apply the stickers in a dry, clean and still environment. Dust, water and wind will make the process a hard task and jeopardise the longevity of the adhesive on the stickers.
- ~ Further clean the area that the stickers are to be applied to with the Isopropyl Alcohol wipe supplied. Grease, oil and dust are a no-no - DO NOT USE WINDOWLENE or WINDEX.
- ~ During despatch the stickers can become slightly raised from the waxy backing liner so it's a good idea to smooth them out with a squeegee (credit card) to make sure the application film is properly adhered to the decals.
- ~ Having chosen where you'd like your stickers to be positioned, apply masking tape to the four corners of the application/transfer film covering the decal and if necessary use a tape measure / ruler to make sure it's centred and as level as you'd like it. If it's a large decal we recommend applying strips of masking tape also at intervals along the edges.
- ~ Do not fully remove the backing liner on your decal. Start by lifting either the bottom left or right corner masking tape to enable you to peel about 10cm of the backing liner away from the vinyl decal and application film and cut this backing liner away. Now you can anchor the decal to the car by pressing that area of the decal against the car/window making sure that everything is still nicely lined up.
- ~ You can slowly pull back more of the waxy backing liner from there on, whilst at the same time applying the decal with the squeegee. Either work left to right or right to left, whichever you feel best doing.
- Note: If the decal is longer than a foot or so, stick the middle of the decal down first, then rub towards one end. Then go back to the middle and rub towards the opposite end. This should reduce the chance of your decal wrinkling.
- ~ Once the decal is stuck to your required surface you can then slowly remove the top application film.